

MATERIAL SAFETY DATA SHEET

DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE
CHICAGO, ILLINOIS 60638
TELEPHONE: (708) 496-7350
FAX: (708) 496-7367

EMERGENCY CONTACT:
CHEMTREC (800) 424-9300

HMIS HAZARD RATING

HEALTH	1
FIRE	2
REACTIVITY	0
PERSONAL PROTECTION	D

Date of Review: February 11,2011
Date of Preparation: December 1990

Revised: May 15, 2008
By: R. Lauterbach

SECTION I: PRODUCT IDENTIFICATION

Product Name: **NOX-RUST® X-110**
Chemical Family: Petroleum Solvent/Additive Blend
Material Usage: Corrosion Preventive Compound

EMERGENCY OVERVIEW: Petroleum solvent-based product with solvent odor. Combustible liquid; when product burns it releases typical hydrocarbon products of combustion. Refer to Section 3 for health effects and to Section 5 for fire hazard data.

SECTION II: HAZARDOUS INGREDIENTS

Component	Wt%	Recommended Exposure Limits (TWA)
Aliphatic Petroleum Solvent CAS #64742-88-7 and/or #64742-47-8 and/or #8052-41-3	41-44	OSHA PEL: 100 ppm ACGIH TLV: 100 ppm ACGIH STEL: 200 ppm
Petroleum Hydrocarbon Distillate CAS #8008-20-6 and/or #64742-88-7	<5	OSHA PEL: 500 ppm
Oxidized Aliphatic Petroleum Fraction CAS #64743-01-7	40-44	OSHA PEL: 2 mg/m ³ (for Wax Fumes)
Petroleum Oil CAS # Not Available	<5	OSHA PEL: 5 mg/m ³ (for Oil Mists)
Calcium Hydroxide CAS #1305-62-0	<5	OSHA PEL: 5 mg/m ³ ACGIH TLV: 5 mg/m ³ (^[1] Nuisance Dust)

^[1] This component poses a hazard only if a dust is formed, i.e., by sawing, sanding, drilling, etc.

SECTION III: HEALTH HAZARD INFORMATION

Primary Routes of Entry: Inhalation, skin absorption.

Acute Effects: Excessive inhalation may produce dizziness, nausea, headache, and incoordination. May cause severe eye irritation and reversible skin irritation. Prolonged skin exposure may cause dermatitis or oil acne. Breathing mists may cause dizziness or pulmonary irritation.

Chronic Effects: Not Determined

Carcinogenicity: None of the components of this product are listed as carcinogens by NTP, IARC, or OSHA 1910(Z).

Pre-Existing Medical Conditions Aggravated by Exposure: Exposure may aggravate pre-existing respiratory or skin problems.

SECTION IV: FIRST AID PROCEDURES

Inhalation: Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

Eyes: In case of contact with material, immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.

Skin: Wash skin with soap and water. Remove and isolate contaminated clothing and shoes at the site.

SECTION V: FIRE AND EXPLOSION HAZARD DATA

Flash Point: 105 °F. Min. (TCC)

Explosive Limits: LEL: 0.6 UEL: 7.0

EXTINGUISHING MEDIA:

Small Fires: Dry chemical, CO₂, water spray, or regular foam.

Large Fires: Water spray, fog, or regular foam. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks. For massive fire in cargo area, use unmanned hose holder or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

Special Firefighting Protection/Emergency Action: Fire may produce irritating or poisonous gases. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Isolate for 1/2 mile in all directions if tank, rail car or tank truck is involved in fire. If runoff from fire control occurs, notify the appropriate authorities.

Unusual Fire/Explosion Hazards: Flammable/combustible material; may be ignited by heat, sparks or flames. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Products of Combustion: Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

SECTION VI: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Steps to be taken in case Material is Released or Spilled: Shut off ignition sources; no flares, smoking or flames in hazard area. Stop leak if you can do it without risk.

Small Spills: Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills: Dike far ahead of liquid spill for later disposal.

SECTION VII: SAFE HANDLING INFORMATION

Precautions To Be Taken In Handling/Storage: Store in cool, well-ventilated area. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors.

Other Precautions: Never wear contaminated clothing. Launder or dry clean before wearing. Discard oil-soaked shoes. Wash thoroughly with soap and water (waterless hand cleaner may be helpful in removing residues) after use and before smoking or eating. Avoid excessive skin contact.

SECTION VIII: EXPOSURE CONTROLS

Respiratory Protection: NIOSH-approved respirator for organic vapor and mist to control exposure where ventilation is inadequate.

Ventilation: General and local exhaust.

Personal Protective Equipment:

Protective Gloves: Impervious gloves (Viton, PVOH, etc.)

Eye Protection: Safety glasses with sideshields or chemical goggles.

Other Protective Clothing or Equipment: If splashing is anticipated, wear rubber apron and boots or other protective equipment to minimize contact.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Color:	Dark
Appearance:	Viscous Liquid
Odor:	Petroleum Solvent
Boiling Point:	>300 °F.
Evaporation Rate (n-Butyl Acetate=1):	<1
Vapor Pressure (mmHg @ 20 °C):	3.4
Vapor Density (air=1):	>1
Solubility in Water:	Negligible
Specific Gravity:	0.88
pH:	Not Applicable
Percent Volatile by Volume:	60

SECTION X: REACTIVITY HAZARD DATA

Stability: Stable

Incompatibility: Strong acids, oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION XI: TOXICOLOGICAL INFORMATION

No data

SECTION XII: ECOLOGICAL INFORMATION

No data

SECTION XIII: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with state, local and federal regulations. Materials may become a hazardous waste through use. If permitted, incineration may be practiced. Consider recycling solvent.

SECTION XIV: TRANSPORTATION INFORMATION

***** AIR, IMDG, EXPORT OR BULK TRANSPORTATION *****

UN1268, PETROLEUM DISTILLATES N.O.S., (Naphtha Solvent), 3, PGIII

SECTION XV: REGULATORY INFORMATION

Volatile Organic Content: (Calculated Values)

VOC per Gallon: 3.4 lbs/gal
VOC per Gallon Minus Exempt Solvents & Water: 3.4 lbs/gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): D001

EPA Hazard Category (40 CFR Part 370): DELAYED (CHRONIC)
FIRE (COMBUSTIBLE)

SARA TITLE III:

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

<u>Chemical</u>	<u>CAS No.</u>	<u>Wt%</u>
NONE		

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

<u>Chemical</u>	<u>CAS No.</u>	<u>Wt%</u>	<u>RQ/TPO Lbs</u>
NONE			

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

<u>Chemical</u>	<u>CAS No.</u>	<u>Wt%</u>	<u>Final RQ Lbs</u>
Aliphatic Petroleum Solvent	64742-88-7 and/or 64742-47-8 and/or 8052-41-3	41-44	100

CALIFORNIA PROPOSITION 65:

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

<u>Chemical</u>	<u>CAS No.</u>	<u>Estimated Concentration %</u>
NONE		

SECTION XVI: OTHER INFORMATION

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.